

# VPN-Gateway

Highest Level of National and  
High International Approvals



# As a VPN gateway, the SINA L3 Box H 200M-a is a key component of the central IT infrastructure in high-security networks.

The data exchange between the SINA components is securely transmitted via encrypted VPN tunnels. SINA L3 Boxes connect public authority or corporate networks via the Internet. In addition, access to (terminal) servers by SINA clients is provided via pre-switched SINA L3 Boxes, which serve as cryptographic network access points.

The SINA CORE-based SINA L3 Box H 200M-a and its predecessor, the PEPP-based SINA Box H, are the only IP-based encryption systems approved by the German Federal Office for Information Security (BSI) for transmitting classified information up to and including German national GEHEIM and STRENG GEHEIM\*. Furthermore, the devices are approved for NATO SECRET and SECRET UE/EU SECRET. The focus is on national and international military and governmental high-security networks.

The SINA L3 Box H 200M-a is substantially more powerful, lighter and more robust compared to the previous model SINA Box H, especially in terms of SINA CORE. The SINA L3 Box H 200M is flexible in many respects, as can be seen in the reloadable crypto device classes, enhanced temperature ranges, the network interfaces that can be reconfigured directly on the device and more modest

power consumption. Furthermore, online updates for operative parameters are supported for SINA CORE modules. In addition, there is the option of service-friendly batteries replacement.

## IT security concept

The SINA L3 Box H 200M-a is based on a holistic IT security concept. It comprises in particular:

- A ruggedized, intensively tested SINA OS system platform
- Smartcard technology
- IPsec-based cryptography
- SINA CORE crypto module and
- Hardware, firmware and software that are dimensioned and configured in accordance with approval standards.

## Secure system start and operation

The SINA L3 Box software is coreboot-protected and reliably loaded by the flash memory during system start. All initial configuration data and security associations for the SINA L3 Box are stored in a protected area of the SINA Smartcard. When a SINA L3 Box is started, the security associations to the SINA Management and the primary communications-related SINA L3 Boxes are set up as IPsec VPN tunnels. If necessary, additional security associations or configuration data from the SINA Management are loaded. This greatly simplifies configuration, installation and hardware replacement with the SINA L3 Box.

## Systems monitoring

The SINA L3 Boxes log all data related to monitoring during operation. This can be imported into network management systems where it can be processed and/or displayed as required.

## High availability

It is possible to increase the availability and reliability of SINA L3 Boxes by means of redundant configurations. An automatic switchover for example triggers a second SINA L3 Box to take on the functions of the failed SINA L3 Box (hot standby) that was previously active.

SINA L3 Boxes also support geo-redundant and load-balancing configurations. In geo-redundant scenarios, alternative communication channels – which can be prioritised as necessary – run via SINA L3 Boxes in different locations. For load-balancing configurations, the SINA L3 Boxes interact with commercially available load balancers.

## Satellite communication

Use of SINA L3 Boxes requires IP-enabled transport networks, including satellite communication lines. The available bandwidth of the satellite lines is used effectively in tandem with satellite optimisers.

## Management

The SINA L3 Box is configured and controlled centrally by SINA Management. An integrated public key infrastructure (PKI) with associated user management supports essential administrative processes involving SINA Smartcards. This includes, in particular, their personalization, the generation or updating of keys and cryptographic parameters as well as the administration of the associated PINs and PUKs.

## Benefits

- Approved for German national STRENG GEHEIM\*, NATO SECRET and SECRET UE/EU SECRET
- PEPP-compatible
- High-performance
- High availability
- Interchangeable network interfaces
- Comfortable Management



# Approval-related construction classes



SINA L3 Box H 200M-a Z1

SINA L3 Box H 200M-a 27A



Performance data		
Approval	German national GEHEIM, SECRET UE/EU SECRET	German national GEHEIM, STRENG GEHEIM*, SECRET UE/EU SECRET
Boot integrity protection	coreboot	coreboot
Software versions	2.2	2.2
SINA CORE device classes	National v1.0 (PEPP-compatible) EU v1.0 (PEPP-compatible)	National v1.0 (PEPP-compatible) NATO 1.x (PEPP-compatible) EU v1.0 (PEPP-compatible)
Manipulation protection	SINA CORE	SINA CORE
Emission protection	Zone 1	SDIP 27 Level A
Authentication token	SINA Smartcard	SINA Smartcard

## Technical data of both model variants

General data	
Design	19" 2 HE
Weight	11 kg
Power consumption	90 W
BTU/h	205
Cryptography	
Module	SINA CORE 100
Encryption performance	180 MBit/s bidirectional
Symmetrical encryption process	Libelle
Asymmetrical encryption process	EC-GDSA, EC-DH
LAN connections	
Network interfaces	3 x 100/1000 MBit LWL optical fibre (switchable) 1 x 100/1000 MBit LWL in SINA CORE (switchable)
Plug type	LC
Temperature ranges	
Operation	+5 °C bis +45 °C
Transport and storage	-20 °C bis +60 °C
Miscellaneous	
Service hatch	For battery replacement

\*In usage situations where data classified as German national STRENG GEHEIM is being processed, the usage scenario and IT security concept for the SINA L3 Box H 200M must be specifically agreed with the German Federal Office for Information Security (BSI).

### Sources

Public authority customers can acquire the SINA L3 Box H 200M-a via the framework contract 5070 "SINA Family Cryptographic Devices" with the Procurement Office of the German Federal Ministry of the Interior, or through SINA supplemental contract Q/IB1C/R6359 with the German Federal Armed Forces. secunet would also be pleased to serve all other national and international customers.

### secunet Security Networks AG

Kurfürstenstraße 58 · 45138 Essen · Germany  
T +49 201 5454-0 · F +49 201 5454-1000  
info@secunet.com · secunet.com

More information:  
[secunet.com/sina](https://secunet.com/sina)